

ALIMENTATORE MEAN WELL CORRENTE COSTANTE - IP42

PROTEZIONE DA SOVRATENSIONE

IP42



WWW.MEANWELL.COM



41.ASD0120936MW



41.ASD0161242MW



41.ASD0252570MW



41.ASD0251550MW



41.ASD0251136MW



41.ASD0352899MW

CODICE	41.ASD0120936MW	41.ASD0161242MW	41.ASD0252570MW	41.ASD0251550MW	41.ASD0251136MW	41.ASD0352899MW
MODELLO	APC-12-350	APC-16-350	APC-25-350	APC-25-500	APC-25-700	APC-35-350
CORRENTE USCITA	350mA	350mA	350mA	500mA	700mA	350mA
POTENZA	12.6W	16.8W	24.5W	25.2W	25.2W	35W
RANGE TENSIONE	9~36V	12~48V	25 ~ 70V	15~50V	11 ~ 36V	28 ~ 100V
TENSIONE INGRESSO	90~264Vac 127~370Vdc	90~264Vac 127~370Vdc	90~264Vac 127~370Vdc	90~264Vac 127~370Vdc	90~264Vac 127~370Vdc	90~264Vac 127~370Vdc
DIMENSIONI	77*40*29mm (W*H*D)	77*40*29mm (W*H*D)	84*57*29.5mm (W*H*D)	84*57*29.5mm (W*H*D)	84*57*29.5mm (W*H*D)	84*57*29.5mm (W*H*D)