

## ALIMENTATORE MEAN WELL DA BINARIO DIN RAIL

### PROTEZIONE DA SOVRACCARICO E DA SOVRATENSIONE



WWW.MEANWELL.COM



41.AS501512MW



41.AS506012MW



41.AS510012MW



41.AS506024MW



41.AS510024MW

Esempio applicativo con binario



CODICE	41.AS501512MW	41.AS506012MW	41.AS510012MW	41.AS506024MW	41.AS510024MW
MODELLO	HDR-15 12	HDR-60 12	HDR-100 12	HDR-60 24	HDR-100 24
TENSIONE USCITA	12V	12V	12V	24V	24V
POTENZA	15W	54W	85,2W	60W	92W
RANGE ADJ	10,8~13,8V	10,8~13,8V	12 ~ 13V	21,6~29V	24 ~ 25.5V
TENSIONE INGRESSO	85~264Vac 120~370Vdc	85~264Vac 120~370Vdc	85~264Vac 120~370Vdc	85~264Vac 120~370Vdc	85~264Vac 120~370Vdc
DIMENSIONI	17.5*90*54.5mm (W*H*D)	52.5*90*54.5mm (W*H*D)	70*90*54.5mm (W*H*D)	52.5*90*54.5mm (W*H*D)	70*90*54.5mm (W*H*D)