

**ALIMENTATORI METALLICI, 12 E 24VDC - MEAN WELL**

**ALIMENTATORI METALLICI  
SOVRACCARICO,  
CORTO CIRCUITO E SOVRATENSIONE**



**12V**

**72W**

41.AS307512MW



**12V**

**102W**

41.AS310012MW



**12V**

**150W**

41.AS315012MW



**24V**

**76,8W**

41.AS307524MW



**24V**

**108W**

41.AS310024MW



**24V**

**156W**

41.AS315024MW

CODICE	41.AS307512MW	41.AS310012MW	41.AS315012MW	41.AS307524MW	41.AS310024MW	41.AS315024MW
MODELLO	LRS-75-12	LRS-100-12	LRS-150-12	LRS-75-24	LRS-100-24	LRS-150-24
TENSIONE INGRESSO	85 - 264Vac 120 - 373Vdc	85 - 264Vac 120 - 373Vdc	85 - 264Vac 240 - 370Vdc	85 - 264Vac 120 - 373Vdc	85 - 264Vac 120 - 373Vdc	85 - 264Vac 240 - 370Vdc
TENSIONE CORRENTE USCITA	12Vdc / 6A	12Vdc / 8,5A	12Vdc / 12.5A	24Vdc / 3.2A	24Vdc / 4,5A	24Vdc / 6.5A
POTENZA	<b>72W</b>	<b>102W</b>	<b>150W</b>	<b>76,8W</b>	<b>108W</b>	<b>156W</b>
EFFICIENZA	89%	88%	87.5%	90%	90%	89%
DIMENSIONI	99x97x30mm	129x97x30mm	159x97x30mm	99x97x30mm	129x97x30mm	159x97x30mm